

# LEDinspect SLIM MAX1000

Inspectionlights



### Dimmer Switch

Individually adjustable brightness levels with up to 1000 lm




### 1000 Lumen

Bright, white LED light and uniform light distribution



### Multi-Angle Light Output

High flexibility due to individual adjustment of the light beam



### 2-year-OSRAM guarantee\*

Systematic quality assurance measures underpin the premium workmanship and functionality of our products. Innovative technology and excellent quality really pay dividends for our customers

## Product datasheet



### Light is versatile

This high-quality inspection light is perfect for professional and private use. With an integrated dimmer, you can select the appropriate brightness level with up to 1000lm for the task at hand with the SLIM MAX 1000. The ultra slim design combined with multi-angle positioning gives maximum flexibility and adjustability to give light exactly where needed. The SLIM MAX 1000 is rechargeable and cordless with Li-ion battery and can therefore provide constant light output. The lamp has an operating time of up to 1.5h with high light output or up to 10,5h with low light output. Charging cable and mains adaptor are included in the scope of supply. In accordance with the IP protection class IP65, this inspection light has protection against the ingress of dust and water and is tested for impact resistance in accordance with IK06. This inspection light has an integrated hook and magnets for hands-free work, making it ideal as a light for manual tasks, car repairs and for everyday use. In addition, OSRAM grants a 2-year guarantee on this product\*

# Product datasheet

## Technical data

### Product information

Order reference	LEDIL410
Application (Category and Product specific)	LED inspection lights

### Electrical data

Nominal wattage	10.00 W
Nominal voltage	3.7 V


### Photometrical data

Color temperature	6000 K
Luminous flux	1000 lm
Light color LED	White

### LED module information

Number of LEDs per module	2
---------------------------	---

### Dimensions & weight



Product weight	308.00 g
Length	365.0 mm
Width	65.0 mm
Height	50.0 mm

### Colors & materials

Base color	Black / Orange
------------	----------------

### Lifespan

Guarantee	2 years
-----------	---------

## Product datasheet

### Additional product data

Type of Battery	Rechargeable
Number of included batteries	1
Scope of battery	Yes
Battery	High-quality lithium-ion battery

### Capabilities

Technology	LED
------------	-----

### Certificates & standards

Standards	CE/EMC/MSDS/ROHS
IK Class	IK06

### Country specific categorizations

Order reference	LEDIL410
-----------------	----------

### Environmental information

Date of Declaration	06-12-2021
Primary Article Identifier	4052899622913
Candidate List Substance 1	No declarable substances contained
CAS No. of substance 1	No CAS
Declaration No. in SCIP database	No declarable substances contained



Detail



Detail

### Logistical Data



Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
--------------	---------------------	---------------------------------	---	--------	--------------

## Product datasheet

4052899622913	INSPECTION LAMP	Folding carton box 1	90 mm x 72 mm x 370 mm	2.40 dm <sup>3</sup>	731.00 g
4052899624030	INSPECTION LAMP	Shipping carton box 6	395 mm x 295 mm x 175 mm	20.39 dm <sup>3</sup>	7306.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File	
	User instruction LEDinspect SLIM MAX 1000
	Movie application LEDinspect Inspection Lights Trailer

#### Application advice:

For more detailed application information and graphics please see product datasheet and user instruction

\*for precise conditions please refer to:

[www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# OSRAM