



WT-600 3G GPS Vehicle Tracker

WT-600 3G GPS Multifunctional Device

WT-600 3G gets you a step ahead with 3G capabilities and better tracking, ideal for fleet tracking and management. Utilizing cutting-edge GPS technology, the WT-600E features not only traditional tracking functions as tele-cutoff petrol, geo-fence, SOS alarm, over speed alert, but optional digital outputs for door detection, vehicle pinpoint by audio-visual alert, external power voltage etc.



Features

- **Remotely cut off fuel/power**
Compel the vehicle to stop by breaking off the fuel connection
- **ACC detection for ignition status**
Be aware of the ignition status whenever you need
- **WCDMA & GSM**
Use 3G network (outstanding coverage, no 2G worries)
- **Tracked by: SMS, APP, Web**
Reports location in real time through different interfaces
- **Configurable tracking modes**
Location uploaded following fixed distance, time interval, preset cornering
- **Multiple alarms**
Instant alert for vibration, over speed, power off, geo-fence
- **SOS emergency call**
Thumb sized button allowing urgent call during an emergency case



Specifications

GSM Specification

Communication System	WCDMA/GSM
Frequency	WCDMA 850/900/1900/2100MHz GSM 850/900/1800/1900MHz
Networks	WCDMA /EDGE/GPRS
Output Power	Class 3 (24dBm +1/-3dB) for UMTS bands Class 4 (33dBm ±2dB) for GSM 850/900MHz Class 1 (30dBm ±2dB) for GSM 1800/1900MHz

GPS Specification

GPS	MTK high sensitivity GPS chip
Frequency	L1,1575.42MHz C/A code
Channels	66
Location Accuracy	<10 meters
Tracking Sensitivity	- 165dBm
Location time	Hot start : ≤1sec(open sky)



Function & Package

Monitoring Scope	≤ 5M
Antenna	Built-in GPS ceramic antenna; GSM quad-band antenna
LED Indicator	GPS(blue), GSM(green), Power(red)
Operating Voltage	9-36VDC
Operating Temperature	450mAh/3.7V industrial lithium polymer battery
Operating Humidity	5%~95%, non-dense
Built-in Battery	450mAh/3.7V industrial lithium polymer battery
Standby	4 hour
Dimension	98(L) ×52.0 (W) ×15.0 (H) mm
Weight	80g