Printing date: 23.05.2017

*

*

Version: 9

Revision: 22.05.2017

| Printing date: 23.05.2017 | Version: 9 | Revision: 22.05.2017 |
|---|--|---|
| SECTION 1: Iden | ntification of the substance/mixture and o | f the company/undertaking |
| · 1.1 Product identifier | | |
| · Trade name: <u>Basta E</u> | ngine Cleaner | |
| No further relevant info Sector of Use SU3 Industrial uses: U SU21 Consumer uses SU22 Professional us Product category PC3 Process category PROC7 Industrial spr PROC11 Non industr | d uses of the substance or mixture and uses advis ormation available. Uses of substances as such or in preparations at indu- : Private households / general public / consumers es: Public domain (administration, education, enterta 35 Washing and cleaning products (including solve aying | strial sites ainment, services, craftsmen) |
| 1.3 Details of the supple Manufacturer/Suppli Basta Active Car Care 2820 Gentofte Denmark Tel: +45 45 881 882 Fax: +45 45 873 874 E-mail: info@bastacare | A/S | |
| | obtainable from: info@bastacarcare.dk | |
| · 1.4 Emergency teleph | one number: During normal opening hours: Tel: +4 | 45 45 881 882 |
| · 2.1 Classification of the | ards identification he substance or mixture ing to Regulation (EC) No 1272/2008 ne | |
| Aerosol 1 H222-H2 | 29 Extremely flammable aerosol. Pressurised contai | iner: May burst if heated. |
| GHS05 corr | osion | |
| Eye Dam. 1 H318 | Causes serious eye damage. | |
| Asp. Tox. 1 H304 | May be fatal if swallowed and enters airways. | |
| | o Regulation (EC) No 1272/2008 ed and labelled according to the CLP regulation. | |
| | | |
| GHS02 GHS05 | | |
| · Signal word Danger | | |
| · Hazard-determining | components of labelling: 3,n-alkanes,cyclic,<2% aromates, Benzene <0.1% | (Contd. on page 2) |
| | | GB |

GB

Safety data sheet according to 1907/2006/EC, Article 31

Printing date: 23.05.2017

Version: 9

Revision: 22.05.2017

Trade name: Basta Engine Cleaner

| | (Contd. of page 1) |
|----------------------|--|
| amiden, C12-1 | 8- en C18-onverzadigde, N,N-bis(hydroxyethyl)- |
| Fatty alcohol p | olyglycolether |
| Polyoxyethyler | ne (7) tridecyl ether |
| Hazard staten | nents |
| H222-H229 Ex | stremely flammable aerosol. Pressurised container: May burst if heated. |
| H318 Ca | auses serious eye damage. |
| Precautionary | <i>y</i> statements |
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P260 | Do not breathe spray. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P273 | Avoid release to the environment. |
| P280 | Wear protective gloves / eye protection. |
| P301+P310 | IF SWALLOWED: Immediately call a doctor. |
| P304+P340 | IF INHALED: Remove person to fresh air and keep comfortable for breathing. |
| P305+P351+P3 | 338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if |
| | present and easy to do. Continue rinsing. |
| P331 | Do NOT induce vomiting. |
| P403 | Store in a well-ventilated place. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| Additional inf | |
| | ated exposure may cause skin dryness or cracking. |
| 2.3 Other haza | |
| | Γ and vPvB assessment |
| PBT: Not appl | icable. |
| vPvB. Not app | licable |

• **vPvB:** Not applicable.

SECTION 3: Composition/information on ingredients

*

· 3.2 Mixtures
· Description: Cleansing agent

| · Dangerous component | s: | |
|-----------------------|--|----------|
| EC number: 918-481-9 | Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1% | 50-<75% |
| | Asp. Tox. 1, H304 | |
| CAS: 106-97-8 | butane (containing < 0.1% butadiene (203-450-8)) | 10-<25% |
| EINECS: 203-448-7 | Flam. Gas 1, H220; Press. Gas (Comp.), H280 | |
| CAS: 74-98-6 | propane | 2.5-<10% |
| EINECS: 200-827-9 | Flam. Gas 1, H220; Press. Gas (Comp.), H280 | |
| CAS: 90622-74-5 | amiden, C12-18- en C18-onverzadigde, N,N-bis(hydroxyethyl)- | 1-<2.5% |
| EINECS: 292-477-9 | Eye Dam. 1, H318; Aquatic Chronic 2, H411; Skin Irrit. 2, H315 | |
| CAS: 68439-50-9 | Fatty alcohol C12-C14 with approx. 2 moles EO | 0.25-<1% |
| NLP: 500-213-3 | Aquatic Acute 1, H400; Eye Irrit. 2, H319; Aquatic Chronic 3, H412 | |
| | | |

| · Ingredients according to detergents guidline 648/2004/EC | |
|--|--------------------|
| aliphatic hydrocarbons | ≥30% |
| non-ionic surfactants | <5% |
| | (Contd. on page 3) |

Printing date: 23.05.2017

Version: 9

Revision: 22.05.2017

Trade name: Basta Engine Cleaner

· Additional information:

(Contd. of page 2)

SECTION 4: First aid measures

· 4.1 Description of first aid measures

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact: Rinse opened eye for several minutes under running water.
- · After swallowing: Do not induce vomiting; call for medical help immediately.
- · 4.2 Most important symptoms and effects, both acute and delayed No further relevant information available.
- · 4.3 Indication of any immediate medical attention and special treatment needed No further relevant information available.

SECTION 5: Firefighting measures

· 5.1 Extinguishing media

- · Suitable extinguishing agents:
- Water haze Fire-extinguishing powder Carbon dioxide
- Alcohol resistant foam
- · For safety reasons unsuitable extinguishing agents: Water with full jet
- · 5.2 Special hazards arising from the substance or mixture
- Nitrogen oxides (NOx)
- Carbon monoxide (CO)
- Sulphur dioxide (SO2)
- No further relevant information available.
- · 5.3 Advice for firefighters
- · Protective equipment: Mount respiratory protective device.

SECTION 6: Accidental release measures

- · 6.1 Personal precautions, protective equipment and emergency procedures
- Wear protective equipment. Keep unprotected persons away.
- · 6.2 Environmental precautions:
- Do not allow product to reach sewage system or any water course.
- Inform respective authorities in case of seepage into water course or sewage system. Do not allow to enter sewers/ surface or ground water.
- · 6.3 Methods and material for containment and cleaning up: Ensure adequate ventilation. Do not flush with water or aqueous cleansing agents
- · 6.4 Reference to other sections See Section 7 for information on safe handling. See Section 8 for information on personal protection equipment. See Section 13 for disposal information.

SECTION 7: Handling and storage

· 7.1 Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace. Open and handle receptacle with care.

(Contd. on page 4)

GB

Printing date: 23.05.2017

*

Version: 9

Revision: 22.05.2017

| Trade name: Basta Engine Clean | er |
|--------------------------------|----|
|--------------------------------|----|

| T. C | 1 4 00 - | | (Contd. of page 3 |
|--|--|-------------|---|
| | about fire - and | | |
| | sources away - D | | ncandescent material. ke |
| | t electrostatic cha | | |
| Pressurised co | ontainer: protect f | from sunlig | th and do not expose to temperatures exceeding 50 °C, i.e. electric |
| lights. Do not | pierce or burn, e | ven after u | se. |
| | s for safe stora | ge, includi | ng any incompatibilities |
| · Storage: · Requirement | s to be met by st | orerooms | and receptacles: |
| Store in a cool | - | orerooms | and receptions. |
| | | | ckagings with pressurised containers. |
| | | | non storage facility: |
| | al regulations on mation about st | | ckagings with pressurised containers. |
| | le tightly sealed. | orage con | untons. |
| Do not seal re | ceptacle gas tight | t. | |
| | dry conditions in | | d receptacles. |
| | neat and direct su | | nt information available. |
| , o specific ti | 14 use(s) 140 full | | |
| (ID OFFICIAL | 0.5 | | |
| SECTION | 8: Exposure | controls/ | personal protection |
| · Additional in | formation abou | t design of | technical facilities: No further data; see item 7. |
| · 8.1 Control p | arameters | | |
| | | that requi | ire monitoring at the workplace: |
| • | | - | ic,<2% aromates, Benzene <0.1% |
| * | erm value: 1200 i | | |
| 106-97-8 buta | ane (containing | < 0.1% bu | tadiene (203-450-8)) |
| WEL Short-te | erm value: 1810 | mg/m³, 750 |) ppm |
| | erm value: 1450 r | | |
| , | f more than 0.1% | of buta-1. | 3-diene) |
| 74-98-6 propa | | / 3.000 | |
| | erm value: 3600 i erm value: 1800 i | | |
| · DNELs | | | • hhm |
| | midan C12 19 | on C18 or | verzadigde, N,N-bis(hydroxyethyl)- |
| | | | 25 mg/kg bw/day (Consumer) |
| | • | - | 5 mg/kg bw/day (Consumer) |
| | The Long Com-s | - | 16 mg/kg bw/day (Worker) |
| | VEL Long term-lo | | 056 mg/cm2 (Consumer) |
| | TEL LONG term-10 | | 056 mg/cm2 (Consumer) 09 mg/cm2 (Worker) |
| Inholative DN | JEL Long town - | | 1.73 mg/m3 (Consumer) |
| minarative DN | TEL LONG term-s | - | 3.4 mg/m3 (Worker) |
| | | /3 | |
| • PNECs | midon (12.10 | on (10 - | vouradiada NN his(hydramothal) |
| | | | verzadigde, N,N-bis(hydroxyethyl)- |
| PNEC Freshw | | - | y/l (Undefind) |
| DNECM | | | |
| PNEC Marine | | | ng/l (Undefind) |
| PNEC Marine PNEC Freshw PNEC Intermi | vater sediment | 0.035 mg | g/kg (Undefind) g/kg (Undefind) ng/l (Undefind) |

⁽Contd. on page 5) GB

Printing date: 23.05.2017

Version: 9

Revision: 22.05.2017

Trade name: Basta Engine Cleaner

| PNEC Soil | (Contd. of page |
|---|---|
| | 0.153 mg/kg (Undefind) |
| PNEC Sewage Treatment Plant | - |
| PNEC Marine water sediment | not expected (Undefind) |
| Additional information: The l | lists valid during the making were used as basis. |
| In case of brief exposure or low use self-contained respiratory p Filter AX/P2 Filter A/P2 Protection of hands: | nic measures: at the end of work. erosols. ive device in case of insufficient ventilation. y pollution use respiratory filter device. In case of intensive or longer exposure |
| Protective gloves | |
| and varies from manufacturer to resistance of the glove material application. Nitrile rubber, NBR Recommended thickness of the Penetration time of glove mat For continuous contact we reco preference given to a breakthro recommend the same. We are a In that case, a shorter breakthro timely replacement are followed | |
| the gloves are made. | ance, because this depends on the exact composition of the material from which is to be found out by the manufacturer of the protective gloves and has to be |

(Contd. on page 6)

Printing date: 23.05.2017

Version: 9

Revision: 22.05.2017

Trade name: Basta Engine Cleaner

(Contd. of page 5)

| 9.1 Information on basic physical and cl | hemical properties |
|--|--|
| General Information | |
| · Appearance: | |
| Form: | Aerosol |
| Colour: | According to product specification |
| · Odour: | Characteristic |
| · Odour threshold: | Not determined. |
| · pH-value: | Not determined. |
| · Change in condition | |
| Melting point/freezing point: | Undetermined. |
| Initial boiling point and boiling range | :-44.5 °C |
| · Flash point: | -97 °C |
| · Flammability (solid, gas): | Not applicable. |
| · Auto-ignition temperature: | Product is not selfigniting. |
| · Explosive properties: | Product is not explosive. However, formation of explosive air/ |
| | vapour mixtures are possible. |
| · Explosion limits: | |
| Lower: | 0.7 Vol % |
| Upper: | 10.9 Vol % |
| · Vapour pressure at 20 °C: | 2100 hPa |
| · Density at 20 °C: | 0.71 g/cm ³ |
| · Relative density | Not determined. |
| · Vapour density | Not determined. |
| · Evaporation rate | Not applicable. |
| · Solubility in / Miscibility with | |
| water: | Not miscible or difficult to mix. |
| Partition coefficient: n-octanol/water: | Not determined. |
| · Viscosity: | |
| Dynamic: | Not determined. |
| Kinematic: | Not determined. |
| | |
| Solvent content: Organic solvents: | 05.7.9/ |
| • 9.2 Other information | 95.7 % |
| 9.4 Other information | No further relevant information available. |

SECTION 10: Stability and reactivity

• 10.1 Reactivity No further relevant information available.

· 10.2 Chemical stability

• Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.

• 10.3 Possibility of hazardous reactions No dangerous reactions known.

 \cdot 10.4 Conditions to avoid No further relevant information available.

 \cdot 10.5 Incompatible materials: No further relevant information available.

 \cdot 10.6 Hazardous decomposition products: No dangerous decomposition products known.

(Contd. on page 7)

GB

Printing date: 23.05.2017

Version: 9

Revision: 22.05.2017

Trade name: Basta Engine Cleaner

(Contd. of page 6)

SECTION 11: Toxicological information

· 11.1 Information on toxicological effects

• Acute toxicity Based on available data, the classification criteria are not met.

\cdot LD/LC50 values relevant for classification:

Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1%

- Dermal LD50 >5000 mg/kg (rabbit)
- Inhalative LC50/4h >4951 mg/l (rat)

90622-74-5 amiden, C12-18- en C18-onverzadigde, N,N-bis(hydroxyethyl)-

Oral LD50 >5000 mg/kg (rat)

· Primary irritant effect:

· Skin corrosion/irritation Based on available data, the classification criteria are not met.

 \cdot Serious eye damage/irritation

Causes serious eye damage.

· Respiratory or skin sensitisation Based on available data, the classification criteria are not met.

· CMR effects (carcinogenity, mutagenicity and toxicity for reproduction)

 \cdot Germ cell mutagenicity Based on available data, the classification criteria are not met.

- \cdot Carcinogenicity Based on available data, the classification criteria are not met.
- \cdot **Reproductive toxicity** Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard

May be fatal if swallowed and enters airways.

SECTION 12: Ecological information

· 12.1 Toxicity

| · Aquatic toxicity: | | | |
|--|--|--|--|
| Hydrocarbons,C10-C13,n-alkanes,cyclic,<2% aromates, Benzene <0.1% | | | |
| EL0 (48h) | 1000 mg/l (Daphnia magna) | | |
| EL0(72h) | 1000 mg/l (Pseudokirchneriella subcapitata) | | |
| LL0(96h) | 1000 mg/l (Oncorhynchus mykiss (96h)) | | |
| 90622-74-5 amiden, C12-18- en C18-onverzadigde, N,N-bis(hydroxyethyl)- | | | |
| LC50 | >1-10 mg/l (Brachydanio rerio) | | |
| NOEC (21 days) | >0.01-0.1 mg/l (Daphnia magna) | | |
| NOEC (28 d) | >0.1-1 mg/l (Oncorhynchus mykiss) | | |
| EC0 | >100 mg/l (Pseudomonas putida) | | |
| · 12.2 Persistence | and degradability No further relevant information available. | | |

• 12.3 Bioaccumulative potential No further relevant information available.

• 12.4 Mobility in soil No further relevant information available.

· Ecotoxical effects:

· Remark: Harmful to fish

· Additional ecological information:

· General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system. Harmful to aquatic organisms

· 12.5 Results of PBT and vPvB assessment

• **PBT:** Not applicable.

(Contd. on page 8)

Printing date: 23.05.2017

Version: 9

Trade name: Basta Engine Cleaner

• **vPvB:** Not applicable.

· 12.6 Other adverse effects No further relevant information available.

SECTION 13: Disposal considerations


· 13.1 Waste treatment methods

· Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· Uncleaned packaging:

· Recommendation: Disposal must be made according to official regulations.



(Contd. of page 7)

Version: 9 Revision: 22.05.2017

Trade name: Basta Engine Cleaner

Printing date: 23.05.2017

| | (Contd. of page |
|---------------------------------------|--|
| Stowage Code | SW1 Protected from sources of heat. |
| 0 | SW22 For AEROSOLS with a maximum capacity of 1 |
| | litre: Category A. For AEROSOLS with a capacity above |
| | 1 litre: Category B. For WASTE AEROSOLS: Category |
| | C, Clear of living quarters. |
| Segregation Code | SG69 For AEROSOLS with a maximum capacity of 1 |
| | litre: Segregation as for class 9. Stow "separated from" |
| | class 1 except for division 1.4. For AEROSOLS with a |
| | capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: |
| | |
| | Segregation as for the appropriate subdivision of class 2. |
| 14.7 Transport in bulk according to A | |
| Marpol and the IBC Code | Not applicable. |
| Transport/Additional information: | |
| ADR | |
| Limited quantities (LQ) | 1L |
| Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| Transport category | 2 |
| Tunnel restriction code | D |
| IMDG | |
| Limited quantities (LQ) | 1L |
| Excepted quantities (EQ) | Code: E0 |
| | Not permitted as Excepted Quantity |
| | |

SECTION 15: Regulatory information

· 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

· Directive 2012/18/EU

· Named dangerous substances - ANNEX I None of the ingredients is listed.

- · Seveso category P3a FLAMMABLE AEROSOLS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 150 t
- \cdot Qualifying quantity (tonnes) for the application of upper-tier requirements $500\ t$
- REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3

· National regulations:

Class Share in %

NK 75-<100

- **VOC-CH** 95.70 %
- **VOC-EU** 677.6 g/l
- Danish MAL Code 5-3
- · 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

SECTION 16: Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· Relevant phrases

H220 Extremely flammable gas.

(Contd. on page 10)

GB

Printing date: 23.05.2017

Version: 9

Revision: 22.05.2017

Trade name: Basta Engine Cleaner

| (Contd. of page 9) |
|---|
| H280 Contains gas under pressure; may explode if heated. |
| H304 May be fatal if swallowed and enters airways. |
| H315 Causes skin irritation. |
| H318 Causes serious eye damage. |
| H319 Causes serious eye irritation. |
| H400 Very toxic to aquatic life. |
| |
| H411 Toxic to aquatic life with long lasting effects. |
| H412 Harmful to aquatic life with long lasting effects. |
| · Department issuing SDS: Research & Development |
| · Contact: info@bastacarcare.dk |
| · Abbreviations and acronyms: |
| RID: Règlement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the |
| International Transport of Dangerous Goods by Rail) |
| ICAO: International Civil Aviation Organisation |
| ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International |
| Carriage of Dangerous Goods by Road) |
| IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association |
| GHS: Globally Harmonised System of Classification and Labelling of Chemicals |
| EINECS: European Inventory of Existing Commercial Chemical Substances |
| ELINCS: European List of Notified Chemical Substances |
| CAS: Chemical Abstracts Service (division of the American Chemical Society) |
| MAL-Code: Måleteknisk Arbejdshygiejnisk Luftbehov (Regulation for the labeling concerning inhalation hazards, Denmark) |
| DNEL: Derived No-Effect Level (REACH) |
| PNEC: Predicted No-Effect Concentration (REACH) |
| LC50: Lethal concentration, 50 percent |
| LD50: Lethal dose, 50 percent |
| PBT: Persistent, Bioaccumulative and Toxic |
| vPvB: very Persistent and very Bioaccumulative |
| Flam. Gas 1: Flammable gases – Category 1 |
| Aerosol 1: Aerosols – Category 1 Press. Gas (Comp.): Gases under pressure – Compressed gas |
| Skin Irrit. 2: Skin corrosion/irritation – Category 2 |
| Eye Dam. 1: Serious eye damage/eye irritation – Category 1 |
| Eye Jam. 1. Serious eye damage/eye irritation – Category 2 |
| Asp. Tox. 1: Aspiration hazard – Category 1 |
| Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard – Category 1 |
| Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 |
| Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard - Category 3 |
| GB |