

...connecting to the aftermarket

CTSTY001.2

Toyota, Lexus Steering Wheel Control Interface









Vehicle Application

Toyota Avensis (T25)	2003 - 2009	Toyota Landcruiser	1998>
Toyota Corolla (T27/E120) 2001 - 2011	Toyota Prado	2007>
Toyota RAV4	2001 - 2011	Toyota Matrix	2003>
Toyota Yaris (XP9)	2001 - 2011	Toyota Vios	2006>
Toyota 4Runner	2002>	Toyota Rush	2006 - 2011
Toyota Avanza	2003>	Toyota Prius	2010>
Toyota Estima	2006>	Toyota Hilux	2004 - 2012
Toyota Previa	2006>	Toyota FJ Cruiser	2001 - 2007
Toyota Fortuner	2005 - 2011	Toyota Auris (E15J)	2003 - 2009
Toyota Innova	2006>	Lexus GX Series (GX 470)	2003 - 2009

Key Features

Retains Steering Wheel Controls

www.connects2.com



ABOUT THIS PRODUCT

CTSTY001.2

Analogue Steering Wheel Control Interface for Toyota and Lexus vehicles with Fujitsu Ten/Matsushita original stereo and 20 Pin connector.

Yellow

Black

Red

WIRING COLOUR CODES

Purple Right Rear Speaker + Purple/Black Right Rear Speaker -Green Left Rear Speaker + Green/Black Left Rear Speaker -Grev Right Front Speaker + Grey/Black Right Front Speaker -White Left Front Speaker + White/Black Left Front Speaker -

Permanent 12V Ground Ignition 12V

PRIOR TO INSTALLATION

Read the manual prior to installation. Technical knowledge is necessary for installation. The place of installation must be free of moisture and away from heat sources. Please ensure that the correct tools are using during the installation to avoid damage to the vehicle or product. Connects2 can not be held responsible for the installation of this product.

TECHNICAL SUPPORT

Connects2 Ltd. want to provide a fast and suitable resolution to any problems encountered during installation of this product. To get in touch with our dedicated technical support team, please fill in a ticket at **support.connects2.com** and provide as much information as possible.

FOLLOW US ON SOCIAL MEDIA for all the latest updates



/CONNECTS2
Watch us on YouTube



Like us on facebook



CONNECTS2LTD Follow us on instagram







FITTING GUIDE

- 1. Remove and disconnect the original head unit.
- 2. Connect the 12 way molex connector of the head unit patch lead (supplied separately) to the interface.





3. Connect the opposite end of head unit patch lead to the head unit steering wheel control input on the back of the aftermarket head unit.

NB: This may be a 3.5mm jack plug or a wire input depending upon the head unit brand being fitted. Please see the head unit installation manual for further information on where to connect.

Important: This step must be completed before connecting power to the interface. Failure to so do may result in no steering wheel control function.



4. Connect the 14 way molex connector to the interface





5. Connect the male power/speaker ISO harness to the female power/speaker ISO harness from the aftermarket head unit. For aftermarket head units without an ISO connector, please refer to "Wiring Colour Codes" on Pg. 2.





FITTING GUIDE

6. Connect the female vehicle specific connectors on the harness to the male vehicle connector from the vehicle. Test head unit for correct operation.

STEERING WHEEL CONTROL FUNCTIONALITY

Original Button	Function
Volume +	Volume +
Volume -	Volume -
Up Arrow	Track +
Down Arrow	Track -
Mode	Source

Example Steering Wheel Control Configuration

(Actual configuration may differ depending on vehicle model)

