

... connecting to the aftermarket

CTUVW02-AMP INFODAPTER



INSTRUCTION MANUAL

www.connects2.com



ABOUT

The Connects2 Infodapter for VW MIB platform vehicles allows vehicle information such as climate control, parking sensors and heated seats to be displayed on any aftermarket head unit with rear camera input. The Infodapter also allows the use of the steering wheel controls with almost every steering wheel control compatible head unit on the market and also retains the OEM amplifier.

DIP SWITCH SETTINGS

See Fig 1.

Up = Off, Down = On


1: On = Pioneer head units. Off = All other head units

2: Setting for reverse camera. On = PAL, Off = NTSC. The default setting is Off (NTSC).

3: Resets the display settings back to default. If the display settings have been manipulated in a way that it is no longer possible to make adjustments, change the DIP switch #3 from Off to On and back. This will reset the screen settings to the factory defaults. During this procedure the screen background will change to red. While the background is red, no settings can be made.


4: Not applicable. (This should be kept in the Up/Off position)

Interface Connections



www.connects2.com

Facia/Steering Wheel Controls



* Shown here are both available facia types


Configuration Menu

aftermarket head unit.

 \sim

To access the menu, **push the 'MENU' button on the fascia panel** (Fig.3) and use the **UP and DOWN buttons to navigate.** Use the **OK** button to select and **Back to go back or exit.**

The Car button will allow access to the vehicle trip computer.



www.connects2.com

Configuration Menu...continued

 Picture Settings -Adjust Brightness, contrast and colour saturation.

Infodapter Settings

Screen Size/Position **Picture Settings** Preferences <Back

o Preferences -

Driver Position - Select Left or Right depending upon vehicle configuration.

Camera Connected - Select Yes if an optional camera is connected.

Reverse Priority* - Select which image (Camera or Park Assist) will be shown by default when reversing. The driver can select the desired image by pushing the Source button (Fig.3) while reversing. (*Note this option is only available when Camera Connected is set to Yes)

Park Brake Source - Set to Speed, Brake or Always On.

Climate - Select how long the climate display should be shown on the head unit when adjusted. Select between the range of 3 seconds and 30 seconds.

Restore factory settings - Reverts all Infodapter settings to factory defaults. (This does not restore vehicle settings)



0

0

Driving Mode -The driving mode button can be used as normal. The graphic for the mode will be shown on the head unit.



Park Assist -The park assist button can be used as normal to activate/decactivate park assist. The graphic will be shown on the head unit.

Legal Information

Please consult the relevant road traffic laws governing the country in which this product is being operated. No liability is accepted for material damage, loss or personal injury, directly or indirectly, from installation and operation of this product. This product should only be operated when safe to do so.

www.connects2.com

Preferences

Driver Position	Right
Camera Connecte	d Yes
Reverse Priority	Park Assist
Park Brake Source	Speed
Climate	5S
Restore factory settings	
< Back	