MOTIP Finishing Putty

Technical Information



Level small, superficial irregularities in surfaces of steel, aluminium, wood and polyester on your car with fast drying MOTIP Finishing Putty. Finishing putty has a fine structure and is easy to sand. MOTIP Finishing putty is re-sprayable with all lacquer systems and can be applied in layers up to 0.5 mm.

Ord.-no: 000063

Quality & properties

Easy to sand
Fast drying
Re-sprayable with all lacquer systems
Very fine structure
Excellent adhesion

Physical & chemical data

Colourname: olive green
Smell: Characteristic
Degree of gloss: mat, 10 ±2
Sandable after: 2-3 h
Flash point: 24-29 °C
Storage stability: 2 years
Content: 250 G

How to use

Before use, carefully read the directions on the packaging and act accordingly.
Processing temperature 15 – 25°C.
The surface should be clean, dry and free of grease. Remove loose old lacquer and rust and sand the surface.
Apply the finishing putty in the desired layer thickness with an applicator.
The drying time depends on the ambient temperature.
After use, directly clean the tools used.

Environmentally sound

European Aerosols is committed to apply formulations without restricted or critical ingredients and to achieve best possible performance. The caps and packagings are made of recyclable material.

Disposal

Only the completely emptied cans should be put into the recycling skip or appropriate container for reclaimable refuse. Cans which are not empty should be disposed off as “special refuse”.

Marking/Labelling

All products made by European Aerosols comply with the actual labelling regulations according to Preparation Guideline 1999/45/EG. All aerosols correspond to TRGS 200 and TRG 300 as well as to aerosol guideline 75/324/EWG in the actually valid version.

As of August 4, 2025 – This release replaces all eventually earlier issued versions.

European Aerosols GmbH, Kurt-Vogelsang-Straße 6, 74855 Haßmersheim – info-de@european-aerosols.com
European Aerosols B.V., Wolfraamweg 2, NL-8471 XC Wolvega – info-nl@european-aerosols.com